

Model		Unit	UMS148C	UMS1412C	UMS1416C	UMS1420C	UMS1424C	UMS1432C
Inputs/Outputs		/	12Sat.,1Terr.,1Sat.D(digiturk)/12Sat.,1Terr.,1Sat.D(digiturk)					
Outputs/Subscribers		/	8	12	16	20	24	32
Frequency Sat.	Sat.	MHz	950~2300	950~2300	950~2300	950~2300	950~2300	950~2300
	Terr.	MHz	47-862(ODM:5-862)					
Sat.Loss(Trunk)		dB	3	4	4	7	7	9
Terr.Loss(Trunk)		dB	3	3	3	4	4	4
Sat.Loss(Tap)		dB	3	3	3	2	2	2
Terr.Loss(Tap)		dB	0	0	0	2	2	3
Switching Isolation		dB	28	28	28	28	28	28
Trunk Isolation		dB	32	32	32	32	32	32
Isolation(Tap)(Sat.)		dB	30	30	30	30	30	30
Isolation(Tap)(Terr.)		dB	25	25	25	25	25	25
Rejection		dB	28	28	28	28	28	28
Return Loss	In	dB	10	10	10	10	10	10
	Out(Trunk)	dB	10	10	10	10	10	10
	Out(Tap)	dB	8	8	8	8	8	8
Sat.Output Level (IMA3-35dB)(Tap)		dBμV	100	100	100	100	100	100
Terr.Output Level (IMA3-60dB)(Tap)		dBμV	88	87	86	86	86	86
Power Supply		VAC/Hz	90-260/47-63					
Max.Current Pass to LNB		mA	1500	1500	1500	1500	1500	1500
Ambient temperature		℃	-20...+50	-20...+50	-20...+50	-20...+50	-20...+50	-20...+50
Dimensions		MM	276*154*50	276*190*50	276*226*50	276*306*50	276*306*50	276*377*50