

Model		Unit	UBMS178E	UBMS1712E	UBMS1716E	UBMS1720E	UBMS1724E	UBMS1732E
Inputs		/	16Sat.,1Terr.					
Outputs/Subscribers		/	8	12	16	20	24	32
Frequency Sat.	Sat.	MHz	950~2250	950~2250	950~2250	950~2250	950~2250	950~2250
	Terr.	MHz	47-862(ODM:5-862)					
Sat.Loss		dB	3	3	3	2	2	2
Terr.Loss		dB	3	3	3	2	0	0
Switching Isolation		dB	28	28	28	28	28	28
Isolation(Sat.)(Out-Out)		dB	28	28	28	28	28	28
Isolation(Terr.)(Out-Out)		dB	25	25	25	25	25	25
Rejection		dB	28	28	28	28	28	28
Return Loss	In	dB	10	10	10	10	10	10
	Out	dB	8	8	8	8	8	8
Sat.Output Level (IMA3-35dB)(Tap)		dBμV	100	100	100	100	100	100
Terr.Output Level (IMA3-60dB)(Tap)		dBμV	88	87	86	86	86	86
Power Supply		VAC/Hz	90-260/47-63					
Max.Current Pass to LNB		mA	2000	2000	2000	2000	2000	2000
Ambient temperature		℃	-20...+50	-20...+50	-20...+50	-20...+50	-20...+50	-20...+50
Dimensions		MM	323*154*50	323*190*50	323*226*50	323*306*50	323*306*50	323*377*50