

Model		Unit	UM34E	UM36E	UM38E	UM312E	UM316E
Inputs		/	2Sat.,1Terr.	2Sat.,1Terr.	2Sat.,1Terr.	2Sat.,1Terr.	2Sat.,1Terr.
Outputs/Subscribers		/	4	6	8	12	16
Frequency	Sat.	MHz	950~2000	950~2000	950~2000	950~2000	950~2000
	Terr.	MHz	47~862(ODM:5~862)				
Sat.Loss		dB	-2	0	1	2	3
Terr.Gain		dB	3	3	0	0	0
Switching Isolation		dB	28	28	28	28	28
Isolation(Sat.) (out-out)		dB	30	30	30	30	30
Isolation(Terr.) (out-out)		dB	25	25	25	25	25
Rejection		dB	28	28	28	28	28
Return Loss	In	dB	11	11	11	11	11
	Out	dB	8	8	8	8	8
Sat.Output Level (IMA ₃ -35dB)(Tap)		dBμV	100	100	100	100	100
Terr.Output Level (IMA ₃ -60dB)(Tap)		dBμV	85	85	85	85	85
Power Supply		V _{AC} /Hz	90~260/47~63				
Max.Current Pass to LNB		mA	500	500	500	500	500
Ambient Temperature		℃	-20...+50	-20...+50	-20...+50	-20...+50	-20...+50
Dimensions		MM	168×138 ×50	168×138 ×50	168×138 ×50	240×138 ×50	240×138 ×50