

Model		Unit	UM44C	UM48C	UM412C	UM416C	UM420C	UM424C	UM432C
Inputs/Outputs		/	4Sat./4Sat.	4Sat./4Sat.	4Sat./4Sat.	4Sat./4Sat.	4Sat./4Sat.	4Sat./4Sat.	4Sat./4Sat.
Outputs/Subscribers		/	4	8	12	16	20	24	32
Frequency Sat.		MHz	950~2300	950~2300	950~2300	950~2300	950~2300	950~2300	950~2300
Sat.Loss(Trunk)		dB	3	3	5	5	7	7	8
Sat.Loss(Tap)		dB	-3	-2	0	0	2	2	3
Switching Isolation		dB	28	28	28	28	28	28	28
Trunk Isolation		dB	32	32	32	32	32	32	32
Isolation Sat.(Tap)		dB	30	30	30	30	30	30	30
Rejection		dB	28	28	30	30	28	28	28
Return Loss	In	dB	11	11	11	11	11	11	11
	Out(Trunk)	dB	11	11	11	11	11	11	11
	Out(Tap)	dB	8	8	8	8	8	8	8
Sat.Output Level (IMA3-35dB)(Tap)		dB μ V	100	100	100	100	100	100	100
Power Supply		VAC/Hz	90-260/47-63						
Max.Current Pass to LNB		mA	800	800	800	800	800	800	800
Ambient temperature		℃	-20...+50	-20...+50	-20...+50	-20...+50	-20...+50	-20...+50	-20...+50
Dimensions		MM	168*138*50	168*138*50	240*138*50	240*138*50	-20...+50	336*138*50	392*138*50