

Model		Unit	UM54P	UM56P	UM58P	UM512P	UM516P
Inputs		/	4Sat.,1Terr.	4Sat.,1Terr.	4Sat.,1Terr.	4Sat.,1Terr.	4Sat.,1Terr.
Outputs/Subscribers		/	4	6	8	12	16
Frequency Sat.	Sat.	MHz	950~2250	950~2250	950~2250	950~2250	950~2250
	Terr.	MHz	47-862(ODM:5-862)				
Sat.Loss		dB	0	2	1	1	2
Terr.Loss		dB	0	0	0	1	2
Switching Isolation		dB	28	28	28	28	28
Isolation(Sat.)(Out-Out)		dB	30	30	30	30	30
Isolation(Terr.)(Out-Out)		dB	25	25	25	25	25
Rejection		dB	28	28	28	28	28
Return Loss	In	dB	11	11	11	11	11
	Out	dB	8	8	8	8	8
Sat.Output Level (IMA3-35dB)(Tap)		dBμV	100	100	100	100	100
Terr.Output Level (IMA3-60dB)(Tap)		dBμV	85	85	85	86	85
Power Supply		VAC/Hz	90-260/47-63				
Max.Current Pass to LNB		mA	800	800	800	800	800
Ambient temperature		℃	-20...+50	-20...+50	-20...+50	-20...+50	-20...+50
Dimensions		MM	225*130*60	225*130*60	225*130*60	290*130*60	295*130*60